

19. (NEW) The apparatus of claim 18 wherein said at least one barrier member comprises from 3 to 4 barrier members.

20. (NEW) The apparatus of claim 10 wherein the minimum distance between said at least one barrier member and said rotary screen is from 4 to 10 mm.

21. (NEW) The apparatus of claim 10 wherein said at least one barrier member comprises the outer surface of said stator.

22. (NEW) Apparatus for separating a fiber suspension through a rotary screen rotatably mounted within a housing, said apparatus comprising a stator mountable centrally within said housing and said rotary screen, said stator including at least one barrier member fixedly attached to said stator and extending axially along the length of said stator.

REMARKS

The above-noted cancellation of claims 1-9, and addition of new claims 10-22, as well as the submission of a new Abstract and revisions to the Specification, are respectfully submitted prior to initiation of the prosecution of this application in the U.S. Patent and Trademark Office.

The above-noted new claims are respectfully submitted in order to more clearly and appropriately claim the subject matter which applicants consider to constitute their inventive contribution. No new matter is included in these amendments. In addition, the revisions to the Abstract and Specification are submitted in order to clarify and correct the Abstract and Specification and to conform them to all of the requirements of U.S. practice. No new matter is included in these amendments.

In view of the above, it is respectfully requested that these amendments now be entered, and that prosecution on the merits of this application now be initiated. If, however, for any reason the Examiner does not believe such action can be taken, it is respectfully requested that he telephone applicant's attorney at (908) 654-5000 in order to overcome any objections which he may have.

Application No. PCT/SE00/00411

If there are any additional charges in connection with this requested amendment, the Examiner is authorized to charge applicant's Deposit Account No. 12-1095 therefor.

Respectfully submitted,

LERNER, DAVID, LITTENBERG,  
KRUMHOLZ & MENTLIK, LLP



ARNOLD H. KRUMHOLZ  
Reg. No. 25,428

600 South Avenue West  
Westfield, NJ 07090-1497  
Telephone: (908) 654-5000  
Facsimile: (908) 654-7866

327048\_1.DOC

093619-01001  
T00T60" E6T9E660

## SCREENING APPARATUS

FIELD OF THE INVENTION

[0001] ~~This~~ The present invention relates to a screening apparatus for separating fiber suspensions, preferably pulp suspensions. ~~The~~ More particularly, the present invention relates to screening apparatus comprises comprising a screen housing and centrally enclosed therein a stator, which is surrounded by a screen means co-axial with the stator and rotary about a rotor shaft. The screen means divides the interior of the screen housing into a screen chamber between the screen housing, and screen means and an accept chamber between the screen means and stator. The screening apparatus further comprises an inlet for the pulp suspension to the screen chamber, a reject outlet for reject from the screen chamber and an accept outlet for accept from the accept chamber.

BACKGROUND OF THE INVENTION

[0002] ~~Such screening~~ Screening apparatus of the type referred to above is used at ~~during~~ the coarse and fine screening of pulp suspensions, preferably for fractionating or separating ~~impurities and other impurities~~ which are not desired to be included in the final product, such as shives, coarse particles, scrap, stones or undigested or ~~not refined~~ unrefined chip bits. The screening apparatus ~~then is~~ usually ~~is~~ pressurized.

[0003] The pulp suspension to be screened is generally introduced ~~via~~ through the inlet to the screen chamber where the approved fraction, i.e., the accept, flows through the rotating screen means. The accept is thereafter discharged through the accept outlet. In order to create suction pulses, pulse elements are provided on the stator. The pulse elements are designed as wings extending in the axial direction along the entire stator and screen means. The wings are arranged in ~~such a manner,~~ such that the pulp suspension can pass between the wings and stator.





member extends radially outwardly from the stator at a predetermined angle. Preferably, the predetermined angle is perpendicular or comprises an angle facing the direction of rotation of the rotary screen.

[00011] In accordance with another embodiment of the apparatus of the present invention, the stator, the rotary screen and the housing each has the shape of a cylinder.

[00012] In accordance with yet another embodiment of the apparatus of the present invention, the rotary screen has the shape of a cone, with an increase in diameter in the direction facing towards the accept outlet.

[00013] In accordance with another embodiment of the apparatus of the present invention, the at least one barrier member comprises from 2 to 8 barrier members, and preferably from 3 to 4 barrier members.

[00014] In accordance with yet another embodiment of the apparatus of the present invention, the minimum distance between the at least one barrier member and the rotary screen is from 4 to 10 mm.

[00015] In accordance with another embodiment of the apparatus of the invention, the at least one barrier member comprises the outer surface of the stator.

[00016] In accordance with the present invention, apparatus is provided for separating a fiber suspension through a rotary screen rotatably mounted within a housing, the apparatus comprising a stator mountable centrally within the housing and the rotary screen, the stator including at least one barrier member fixedly attached to the stator and extending axially along the length of the stator.

[00017] ~~This object is~~ The objects of the present invention are achieved by a screen apparatus ~~of the kind described in the introductory portion,~~ which comprises at least one barrier and pulse element (barrier/pulse element). The barrier/pulse element is located on the stator and extends in the axial direction substantially along the entire stator and the entire screen means, and is capable upon rotation of the screen means

09936193-091001

~~to create in addition to~~ of creating both suction pulses ~~also~~  
~~and pressure pulses with respect~~ to the pulp suspension in the  
screen chamber. The pressure pulses produce a substantially  
radially directed pump effect to the screen means and  
outwardly in the pulp suspension in the screen chamber, so  
that the reject continuously and ~~already~~ directly after the  
~~start~~ beginning of the screen passes through the reject  
outlet. Consequently, substantially no thickened reject layer  
is built up, and the risk of plugging is reduced considerably.  
It is, ~~thus,~~ therefore possible to screen at higher pulp  
concentrations without disturbances.

[00018] The barrier/pulse element, ~~contrary to as contrasted~~  
with the pulse elements of the prior art, is attached tightly  
to the stator and extends from the stator outwardly to the  
screen means, so that the accept is substantially ~~is~~ prevented  
from tangentially passing the barrier/pulse element. The  
accept is thereby forced either to move axially to the accept  
outlet or, due to the pressure pulse, radially to the screen  
means, whereby the screen means is cleaned, and the pulp  
suspension in the screen chamber is mixed with that accept  
portion, which passes out through the screen means.

[00019] In addition to the aforementioned advantages, such a  
screen has proved to yield a uniform quality of the accept,  
even when the ~~injeet~~ injected suspension has a non-uniform  
quality with regard to the content of, for example, shives,  
coarse particles, knots, incompletely digested or unrefined  
chip bits.

~~The characterizing features of the invention are apparent from~~  
~~the attached claims.~~

#### BRIEF DESCRIPTION OF THE DRAWINGS

[00020] The present invention is described in greater detail  
in the following, ~~with reference~~ detailed description, which,  
in turn, refers to the accompanying drawings illustrating ~~an~~  
one embodiment of the present invention, as follows:

[00021] Fig. 1 ~~shows~~ is a side, elevational, partially sectional view of a screening apparatus according to the present invention;

[00022] Fig. 2 is a ~~radial section~~ top, elevational, partially sectional view of the screening apparatus according to the invention, shown in Fig. 1;

[00023] Fig. 3 ~~shows an enlargement~~ is a top, elevational, enlarged, sectional view of the barrier/pulse element shown in Fig. 2;

[00024] Fig. 4 ~~shows~~ is a top, elevational, enlarged, sectional view of another design of the barrier/pulse element shown in Fig. 3;

[00025] ~~Figs. Fig. 5 and 6 show other embodiments~~ is a top, elevational, enlarged, sectional view of another design of the barrier/pulse element, shown in Fig. 3; and

[00026] Fig. 6 is a top, elevational, enlarged, sectional view of another design of the barrier/pulse element shown in Fig. 3.

#### DETAILED DESCRIPTION

[00027] The screening apparatus shown in Fig. 1 comprises a pressurized screen housing I with an upper portion 2, which has a greater diameter than the lower portion 3 of the screen housing. In the upper portion 2 of the screen housing I a substantially tangential inlet 4 is located for the fiber suspension to be separated, which in this example is a pulp

[00028] suspension. An accept outlet 5 for the accept is located substantially tangentially in the lower portion 3 of the screen housing I. A reject outlet 6 is located substantially axially and downwardly directed in the lower side of the upper portion 2, but radially ~~seen~~ outside the lower portion 3.

[00029] In the upper portion 2 of the screen housing a rotationally symmetrical screen means 7 is located so that it is rotary about a vertical rotor shaft 11. A stator 8 is located radially ~~seen~~ inside the screen means 7. The screen means 7 and stator 8 are arranged co-axially. The screen means

0936193-01001

Sub B17

Sub B27

Sub B37



7 defines the upper portion 2 of the screen housing I in a screen chamber 9 between the screen housing I and screen means 7 and an accept chamber 10 between the screen means 7 and stator 8.

[00030] The screen means 7 can be ~~of~~ any type of screen means comprising screen apertures of a suitable size for passing through the desired portion of the pulp suspension. The screen means, for example, can have slits with openings between 0.1 mm and 0.5 mm, or holes with hole diameters between 0.1 mm and 12 mm, and ~~at~~ during coarse screening, preferably from 8- to 10 mm.

[00031] In the lower portion 3 of the screen housing a lower accept chamber 13 is located which constitutes an extension of the accept chamber 10.

[00032] On the stator 8 four barrier/pulse elements 12 are located symmetrically. The barrier/pulse elements 12 can be one or more in number, but are suitably from 2- to 8 and most ~~suitably~~ preferably from 3- to 4, and are advantageously arranged symmetrically in the circumferential direction of the stator 8.

[00033] The barrier/pulse elements 12 extend in the axial direction along the entire stator and are attached tightly to the stator 8. They extend from the stator 8 and out to and along the entire screen means 7. The distance between the barrier/pulse elements 12 and screen means 7 shall be so ~~short~~ small that the accept (accepted suspension) substantially does not pass there between. A suitable minimum distance between the barrier/pulse element 12 and screen means 7 is from 4 to 10 mm. The accept chamber 10 is thereby divided into a number of smaller accept cells 10<sub>1</sub>, 10<sub>2</sub>, 10<sub>3</sub> and 10<sub>4</sub>, each of which communicates with the lower accept chamber 13 in the lower portion 3 of the screen housing and thereby with the accept outlet 5.

[00034] ~~At~~ In the embodiment shown in the drawings, the barrier/pulse elements 12 extend in the axial direction straight downwardly from above. In order to assist in feeding

the accept in the accept 10<sub>1</sub>, 10<sub>2</sub>, 10<sub>3</sub> and 10<sub>4</sub> to the accept outlet 5, the barrier/pulse elements 12 can instead be designed so that, they as axially seen in the direction to the accept outlet 5 (in this example downward from above) they deflect in the rotational direction of the screen means. ~~Hereby~~ In this manner, the accept is guided more easily to the accept outlet 5, and a lower pressure drop above the stator 8 is obtained.

Sub 04  
[00035] The pulp suspension to be separated is fed ~~via~~ through the inlet 4 into the screen chamber 9. The rotating screen means 7 ~~transfers mechanically~~ transfers energy to the pulp suspension in the screen chamber 9, which thereby follows the rotational direction of the screen means at the same time as it moves downwardly and thereby in a screwing movement moves down through the screen chamber 7. When the screen means rotates, a suction pulse arises on the rear side of the barrier/pulse element 12, as seen in the rotational direction. The accepted fraction of the pulp suspension ~~flows~~ thereby flows through the rotating screen means 7 and into one of the accept cells, 10<sub>1</sub>, 10<sub>2</sub>, 10<sub>3</sub> or 10<sub>4</sub>. The main portion of the accept thereafter flows thereafter down to the lower accept chamber 13 and out through the accept outlet 5.

[00036] During the rotation of the screen means 7, the accept in the accept cells, 10<sub>1</sub>, 10<sub>2</sub>, 10<sub>3</sub> and 10<sub>4</sub>, partially follows along in the rotation of the screen means 7. When the accept approaches the barrier/pulse element 12, portions of the accept are pressed back out through the screen means 7 and out into the screen chamber 9. ~~Thereby~~ In this manner, the screen means 7 is cleaned of possible ~~cloggings~~ clogging, and the pulp suspension in the screen chamber 9 is mixed with the accept fraction from the accept chamber 10. ~~Hereby~~ Thus, too heavy a thickening of the pulp suspension in the screen chamber 9 is prevented, and at the same time ~~also a~~ rotation of the accept in the same direction in the accept chamber 10 is prevented.



radial as in Fig. 5 or deflected in the rotational direction of the screen means 7, as in Fig. 6.

Sub B57 [00042] ~~At~~ In the embodiment shown in the drawings, the stator 8, screen means 7 and screen housing I outside the screen means 7 all have the form of a cylinder. One or ~~several~~ more of the stator, screen means and, ~~respectively~~, screen housing outside the screen means can also, for example, have a conical shape, with different or equal ~~angle~~ angular relations relative to one another. By forming the screen housing outside the stator, and, ~~respectively~~, forming the stator cylindrical or conical, it is possible to ~~change~~ alter the accessible space between them. By changing, for example, the screen means from cylindrical to conical in shape, the relationship between accessible space in the screen chamber and, ~~respectively~~, the accept chamber, respectively, can be ~~changed~~ altered. If accessible space ~~thereby~~ in axial direction thus becomes different, the space in the accept chamber should increase in the direction to the accept outlet, and the space in the screen chamber should be greatest at the inlet.

[00043] The accept outlet, reject outlet and inlet, ~~of course~~, can also be located in places in the screening apparatus other than those indicated ~~at~~ in the embodiment shown in the drawings. The accept outlet, for example, can be located in the upper portion of the screening apparatus, and the inlet an be located in the lower portion thereof. The reject outlet is suitably ~~is~~ located in the lower portion of the screening apparatus, in order to utilize the gravity at the separation of heavy foreign particles.

[00044] ~~At a~~ In one variant of the stator, in addition to barrier/pulse elements it can also be provided with pulse elements of a conventional type. It can, for example, be provided with 4 barrier/pulse elements and between them with ~~usual~~ conventional pulse elements, where the accept can pass between the wing and the stator.

[00045] A screening apparatus according to the present invention, ~~of course~~, can also be used separately as well as in combination with other screens in a common screen housing. ~~The invention, of course, is not restricted to the embodiment shown, but can be varied within the scope of the claims with reference to description and Figures.~~

[00046] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

327056\_1.DOC